



Finmatt – soft matting agent range

Description

Finmatt powders are a matting agent combination of organic and inorganic components for use in various coating systems. In addition to its good dispersibility, Finmatt has minimal influence on the binder viscosity.

Surface resistance

Even at high amounts (5 - 10%), the chemical resistance (against alcohol, hand cream, etc.) and mechanical resistance (against marking, polishing) of dull matt surfaces are not impaired.

Anti-Slip

The soft Finmatt range includes different mean particles sizes to adjust to various dry film thicknesses. The matting agents are designed for soft-touch or anti-slip surfaces, not to increase the soft touch effect, but to best retain the soft touch given by the binder.

Range of use

Finmatt may be used in all common binder systems. Especially in water-based coatings the above described effects are recognized.

- Water-based coatings (1pack/2pack)
- UV-coatings (100%, water-, solvent-based)
- Solvent-based coatings (1pack/2pack)

Applications

- Parquet varnishes, floor care products
- Furniture coatings/foils
- Foil coatings
- (Artificial)Leather-Topcoats
- Plastic part coatings
- Glass coatings
- Packaging inks
- Pavement, concrete coatings

Specification

Finmatt	average particle size (D50)
174V	8 ± 3 µm
177V	9.7 ± 3 µm
121V	8 ± 3 µm
151V	9 ± 3 µm
176V	16 ± 3 µm
173V	27 ± 5µm

Typical data general information, not part of the specification

Finmatt	174V	177V	121V	151V	176V	173V
Appearance	- white powder -					
Average particle size D90	approx. 14 µm	approx. 17 µm	approx. 15 µm	approx. 20 µm	approx. 30 µm	approx. 46 µm
soft-touch	●●●	●●○	●○○	●○○	●●●	●●●
Matting efficiency	●○○	●●○	●●●	●●●	●○○	●○○
surface resistance	●●●	●●○	●○○	●○○	●●●	●●●

Further types are available upon request

Packaging Packaging unit 10kg paper bag

Storage

Store at low relative humidity in closed bags. Do not store pallets on top of each other. This could compress the material and destroy application properties. The storage time of 12 month after shipment should not be exceeded.

Contact

- Customer-specific requirements need individual solutions.
- We can offer you support and advice for the start of your development work.
- Do you need more information?
- The FINMA team is looking forward to your contact.

FINMA GmbH

Theodor-Heuss-Straße 5
D - 61191 Rosbach
phone.: +49-6003-9193-0
fax: +49-6003-9193-29
info@finma.de
www.finma.de



This datasheet should advise technically. It is not binding and does not claim to be complete. The above data do not represent a characteristic warranty. The customer is not freed by this datasheet from his obligation to the examination on suitability for the intended purposes and procedures. Same applies to the inspection of incoming goods at the customer.

created 2019-03-05

replaces sheet from 2019-01-21