



## Description

Finma-Sil pastes are aqueous matting agent concentrates with a very broad compatibility in all tested water-based systems, including acrylate and polyurethane dispersions.

Finma-Sil is free-flowing, easy to handle and pumpable.

The amount of wetting agents is reduced to a minimum. Nevertheless, Finma-Sil does not cream even after prolonged storage times and does not sediment. The sedimentation behavior is significantly improved compared to the pure component.

The paste can also enhance the soft feel and the mechanical resistance (against marking, polishing) of the surface.

## Range of use

Finma-Sil pastes are readily dispersed concentrates that can be easily incorporated into existing formulations for matting or final adjustments of the matting degree. High shear rates are not necessary. Finma-Sil is compatible with all water-based systems:

- PU-Dispersions
- Polyester/Alkyd resins
- Amide-/Amine resins
- Acrylate-Dispersions
- Polyepoxide resins
- Aqueous UV coatings

## Applications

- Parquet varnishes, floor care products
- Furniture coatings/foils
- Foil coatings
- (Artificial)Leather-Topcoats
- Plastic part coatings
- Glass coatings
- Packaging inks

## Product details

Finma-Sil	solid content	average particle size (D50)	average particle size (D90)
<b>8-FX 1.5</b>	45	9.1 µm	18.6 µm
<b>15-FX</b>	50	13.2 µm	21.9 µm
<b>8-RX</b>	45	7.4 µm	12.8 µm
<b>30X-5</b>	45	4.4 µm	7.5 µm
<b>8-BX</b>	50	6.9 µm	11.9 µm
<b>20-MG</b>	20	6.5 µm	10.8 µm
<b>30X-5EM</b>	22	4.8 µm	7.5 µm
<b>30X-5W</b>	52	4.8 µm	11.6 µm

## Product details

Finma-Sil	appearance	pH-value	matting degree	Surface feel
<b>8-FX 1.5</b>	white paste	neutral	medium	velvety/soft
<b>15-FX</b>	white paste	neutral	medium	soft/anti-slip
<b>8-RX</b>	White paste	Neutral	medium	medium soft
<b>30X-5</b>	white paste	neutral	medium	silky/smooth
<b>8-BX</b>	white paste	neutral	medium	silky/smooth
<b>20-MG</b>	white paste	neutral	high	smooth
<b>30X-5EM</b>	white paste	neutral	high	silky/smooth
<b>30X-5W</b>	white paste	Neutral	medium/high	silky/smooth

Further types are available upon request

### Packaging

Packaging unit

25 kg plastic drum  
100 kg plastic drum  
1000 kg container (IBC)

### Storage

Store in closed containers at low relative humidity and protected from freezing. Always keep the containers closed. The storage period of six months after shipment should not be exceeded.

It is recommended to homogenize by stirring before use.

## Contact

---

- Customer-specific requirements need individual solutions.
- We can offer you support and advice for the start of your development work.
- Do you need more information?
- The FINMA team is looking forward to your contact.

### FINMA GmbH

Ottostraße 17  
D - 61191 Rosbach  
phone.: +49-6003-9193-0  
fax: +49-6003-9193-29  
[info@finma.de](mailto:info@finma.de)  
[www.finma.de](http://www.finma.de)



This datasheet should advise technically. It is not binding and does not claim to be complete. The above data do not represent a characteristic warranty. The customer is not freed by this datasheet from his obligation to the examination on suitability for the intended purposes and procedures. Same applies to the inspection of incoming goods at the customer.

created 2024-07-04

replaces sheet from 2021-11-25